

Tor Project

A Pi a day, keeps censorship away

You would like to support human rights? Then please follow the how-to.

Note: We assume you have a new working [Arch Linux](#) running on your [RaspberryPi](#).

Installation

First we have to install all the packages which are needed & useful to us.

```
<sxh bash;> root@pi# pacman -Syyu root@pi# pacman -S base-devel vim tor ntp tor vnstat sudo  
</sxh>
```

After that we should create us an own user account with sudo privileges.

```
<sxh bash;> root@pi# useradd -m -s /bin/bash YOUR_USERNAME root@pi# vimsudo /etc/sudoers ...  
</sxh>
```

Now, we install [yaourt](#) in order to fetch and install packages from the AUR.

```
<sxh bash;> root@pi# su YOUR_USERNAME root@pi# wget  
https://aur.archlinux.org/packages/ya/yaourt/yaourt.tar.gz root@pi# tar xfv yaourt.tar.gz root@pi# cd  
yaourt root@pi# makepkg -si root@pi# cd ~/ root@pi# rm -r yaourt* root@pi# yaourt -Syua  
root@pi# yaourt -S arm </sxh>
```

In order to integrate tor into systemd, we need to write a -n own service file, which ensures fast, easy usage and the guarantee that at every boot tor will be started along.

```
<sxh bash;> root@pi# cd /etc/systemd/system root@pi# vim tor.service </sxh>
```

```
<sxh bash; title: systemd service file - /etc/systemd/system/tor.service> [Unit] Description=Starting  
Tor Service
```

```
[Service] ExecStart=/usr/bin/tor -f /etc/tor/torrc
```

```
[Install] After=multi-user.target </sxh>
```

```
<sxh bash;> root@pi# vim ntp-once.service </sxh>
```

```
<sxh plain; title:>
```

```
</sxh>
```

Configuration

After this, we finally attack the most important part: Tor configuration.

```
<sxh bash;> root@pi# cd /etc/tor/ root@pi# mv torrc torrc.original root@pi# vim torrc </sxh>
```

```
<sxh plain; title: /etc/tor/torrc> ORPort 443
```

Log notice file /var/log/tor/notices.log

RelayBandwidthRate 100 KB # Throttle traffic to 100KB/s (800Kbps) RelayBandwidthBurst 200 KB #
But allow bursts up to 200KB/s (1600Kbps)

#AccountingStart day 00:00 #AccountingMax 8 GB

```
SocksPort 0 BridgeRelay 1 Exitpolicy reject *:~</sxh>
```

Up & Run!

Either type:

```
<sxh bash;> root@pi# systemctl start tor </sxh>
```

or simply boot up your device.

References

- [Routing 150GB Tor traffic through a Raspberry Pi](#)

Conclusion

From:

<https://wiki.c3l.lu/> - Chaos Computer Club Lëtzebuerg

Permanent link:

<https://wiki.c3l.lu/doku.php?id=projects:howtos:tor&rev=1368386599>

Last update: **2015/07/15 21:54**

